

# UNIVERSAL-

# TOPPER

# HGM-U/HGM

- For vineyards and orchards

COMPACT AND  
LOW HOUSING

•

MINIMAL DIFFERENCE  
BETWEEN  
MACHINE WIDTH AND  
WORKING WIDTH

•


SMOOTH  
OUTER CASING




## THE UNIVERSAL TOPPER

- The SAUERBURGER UNIVERSAL TOPPER enables you to top and shred chopped wood, prunings and crop remains without changing the cutting tools.
- Quick working with low power, improving fuel economy.
- Optimal shredding through its opposing cutter bar and rake sieve, improving decomposition and humification of the shredded goods. Available with double sided Y flails, wide flails and hammer flails.
- Drive transfer from gearbox to rotor through heavy duty drive belts. Rotor fitted with heavy duty bearings.
- Compact drive transfer housing, smooth outer edges and deflector bars, allowing cutting right up to the plant stem. The deflector bars reduce snagging on the plant stem. Counter sunk bolt heads on the casing also reducing snagging on wires, plants etc.

### Flails HGM-U



Wide Flails



Universal-Y-Flails



Heavy hammer flails for optimal shredding of thicker prunings

### FOR VINEYARDS

Type	Total width m	Working width m	N.r. of Flails		Weight kg
			Wide Flails	Y-Flails	
<b>HGM 950 U</b>	0,95	0,90	8	24	280
<b>HGM 1050 U</b>	1,05	1,00	8	24	300
<b>HGM 1150 U</b>	1,15	1,10	9	27	320
<b>HGM 1300 U</b>	1,30	1,25	12	36	330
<b>HGM 1400 U</b>	1,43	1,35	12	36	380
<b>HGM 1500 U</b>	1,53	1,45	12	36	390
<b>HGM 1650 U</b>	1,68	1,58	16	48	380

### FOR HORTICULTURE

<b>HGM 1550</b>	1,59	1,50	12	450
<b>HGM 1850</b>	1,93	1,78	14	520
<b>HGM 2150</b>	2,15	2,00	16	640
<b>HGM 2450</b>	2,45	2,30	20	690
<b>HGM 2650</b>	2,65	2,30	20	730



Alle Angaben und Abbildungen sind annähernd und unverbindlich. Konstruktionsänderungen behalten wir uns jederzeit vor.

Sales, Service and Advice  
**Sayell Equipment**  
 Little Foxes Farm



### STANDARD FEATURES

- Universal double sided Y-Flails or Wide Flails
- Freewheeling in gearbox
- Opposing cutter bar
- A choice of:- Running Roller or castor wheels
- Rake sieve
- Safety guards and protective flaps on front feeder
- Storage stand

### OPTIONAL EXTRAS

- PTO shaft
- Side shift (HGM 1550 - 2650 standard)
- Hydraulic cylinder and hoses hoses for side shift
- Front and Rear mounting with through-put gearbox  
Double 3-point hitch with side shift
- Front Mounting