

SHREDDER

BE

LARGE FEED OPENING

•

LARGE DIAMETER ROTOR

VERY SHORT SHREDED

PRODUCT ALSO WITH

MAIZE STUBBLE

•

GOOD DISTRIBUTION

OF COMBINE OUTPUT



SAUERBURGER

SHREDDER BE - ECONOMICAL AND LIGHT-RUNNING

The SAUERBURGER straw shredder has a high operational capacity ensuring an efficient redistribution and shredding of straw and stubble. The large feed opening and the high capacity of this machine allows you to rework the product in just one pass. The adjustable output flap and guide plates guarantee the shredded product is evenly distributed behind the machine.

The use of a quick release system on the output flap allows a quick and simple closure of the flap making the machine ready for stubble shredding or maintaining fallow land.

Inside the rotor housing are counter cutters in which the straw is caught and shredded. The close proximity of the flails to the cutter bar guarantees an optimally shredded product that can then be ploughed back into the field.

The quick decomposition and humification of the shredded product gives you an optimal mouldboard and is also effective against parasites.

The height adjustment of the machine is carried out by the 2 running wheels. This guarantees an even cut and reduces contact between the flails and ground.

The drive for the machine is taken care of by a heavy duty gearbox and an oversized power-belt drive (BE 3500 has drive belts on both ends of the rotor). The precision balanced rotor gives a vibration free operation, increasing the working life of the machine. To reduce wear on stony ground and also in high capacity situations, we recommend an impact plate in the rotor housing. This acts as a buffer between the rotor and housing and can be changed when worn out.

STANDARD FEATURES

- Solid welded construction
- Main rotor with 1 set of flails
- 2 Counter cutters
- Adjustable output flap
- Tyres
- Power belt drive from BE 1700 to BE 2600 with mechanical belt tensioner
- BE 3000 and BE 3500 automatic belt tensioner
- PTO shaft

OPTIONAL EXTRAS

- PTO shaft with free-wheeling
- Straw guide plates
- Impact plate
- Large dimension tyres 10.0/75 – 15,3 (standard on BE 3500)



Straw guide plates –
Optional extra



Automatic belt tensioner

Type	Total width mm	Working width mm	Nr. of power belts	N.r. of flails	Weight kg	Power class	PTO Rpm
BE 1700	1,70	1,60	3	20 Pair	480	30 / 40	540
BE 2600	2,60	2,40	4	30 Pair	750	45 / 60	540
BE 3000	3,00	2,80	6	36 Pair	1000	60 / 80	1000
BE 3500 D	3,50	3,20	2x4	40 Pair	1050	75 / 100	1000

Sales Service and Advice



Details and figures stated are approximate and not binding. We reserve the right to proceed to construction modifications at any time.

Im Bürgerstock 3

D-79241 Wasenweiler

Tel. 07668-90320 Fax -7802

e-mail: info@sauerburger.de

www.sauerburger.de