

Large surface

TOPPER

PEGASUS

For efficient mowing of:

- FALLOW LAND
- SET-ASIDE LAND
- FIELDS
- PASTURE LAND

For Topping off and Mulching

- GREEN MANURE
- CROP REMIANS
- MAIZE
- SUNFLOWERS

Large surface
coverage

•
Front mounting

•
Rear mounting

•
Split mounting

•
Trailer type
Rear mounting



Toppers

Shredders

Ploughs

Power harrows

Pulverizer

Vine stem cleaners

Yard Loaders

Tractors

SAUERBURGER

The SAUERBURGER large surface topper PEGASUS with its working width from 6.3m to 9.5m is the ideal machine for a cost effective working of large scale areas. The optimal chopping quality will guarantee a quick decomposition and humification. Pegasus has 3 mowing heads that are independent from another allowing mowing on uneven ground. When being transported, the outside wings fold up hydraulically reducing the amount of time needed to prepare for transport.

STANDARD FEATURES

- Mowing heads - Hydraulically foldable for road transport
- Transport width 3 m • Rotor can be fitted with either Y-flails or wide-flails • Counter cutting inside the housing • Impact plate 3 mm thick • Heavy duty power belts with automatic tensioning
- PTO shaft • Running rollers • Stone impact protection

Only for trailer version:


- Trailer hitch according to request • Axle suspension through nitrogen tank • Tyres 15.0/55-17

Optional Extras:

- Mounting for reversible tractor cabs (free of charge)
- Nitrogen puffer for the wings reducing shock loads (standard on PEGASUS 9500) • PTO with freewheeling
- Air brakes for trailer version • Warning signs


CONVINCING TECHNOLOGY AND PERFORMANCE

The choice of flails depends on the job at hand. With SAUERBURGER you have the choice of:



Universal Y-flails:

Very light running, low power usage, for fallow and set-aside land and crop remains



Wide Flails:

For chopping harder materials like wood pruning, pruning, weeds and also fields and pastures

VARIABLE FORMATS



Trailer Version



Split Version



Rear Mounting



Front Mounting

Type	Working width m	Transport-width m	N.r. of Flails	Rotor diameter on wings	Rotor diameter on middle head	Weight kg	PTO Rpm
PEGASUS 6300	6,30	3,00	156 / 52	490	536	2650	1000
PEGASUS 8000	8,00	3,00	204 / 68	542	536	3160	1000
PEGASUS 9500	9,50	3,00	240 / 80	589	536	4380	1000

Sales service and advice



Details and figures stated are approximate and not binding. We reserve the right to proceed to construction modifications at any time.

Im Bürgerstock 3 D - 79241 Wasenweiler Tel. 07668 - 90320 Fax - 7802

info@sauerburger.de

www.sauerburger.de